

# Certificate of Conformity

Certificate Number: CN-PV-230299

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacturer(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant: Ningbo AUX Solar Technology Co., Ltd.

No. 17 Fenglin Road, Cicheng Town, Jiangbei District, Ningbo City, Zhejiang

Province, China

**Product:** Three phase on grid solar inverter

See appendix of Certificate of Conformity

ASN-5TL, ASN-6TL, ASN-8TL, ASN-10TL, ASN-12TL ASN-15TL, ASN-17TL, ASN-20TL, ASN-23TL, ASN-25TL

AUXSOL Brand Name<s>:

**Product Complies with:** Commission Regulation (EU) 2016/631 of 14 April 2016 (NC RfG) establishing a network code on the requirements for connecting generating units to the

network (Journal of Laws UE L 112/1 of 27 April 2016);

PSE:18 December 2018: General Application Requirements resulting from the Regulation of the EU Commission 2016/631 of April 14, 2016 establishing the network code on the requirements for connecting generating units to the grid approved by the Decision of the President of the Energy Regulatory Office DRE.WOSE.7128.550.2.2018.ZJ of January 2, 2019;

PTPiREE, 2021-04: Conditions and procedures for the use of certificates in the process of connecting power generation modules to power grids.

Type approval for Type A PPMs

**Certificate Issuing Office Name** Intertek Testing Services Ltd. Shanghai

West Area, 2nd Floor, No. 707, Zhangyang Road

China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China

Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012

230509148GZU-001 Test Report No.<s>:

Additional information in Appendix.

Signature

& Address:

**Ratings & Principle** 

**Characteristics:** 

Model:

**Certification Manager: Grady Ye** 

Date: 05 June 2023 Valid until: 04 June 2028

PRD Nº 306B



This is an Appendix to Certificate of Conformity Number: CN-PV-230299

The following functionalities have been assessed based on the rules for the use of certificate for Power Park Modules (PPMs), as specified in chapter 7 and 9 of the PTPIREE 2021-04. The functions denoted "Not Applicable" in the table of chapter 7 has not been included.

| Capability  | NC RfG  | PSE 2018-12     | Туре А | Assessment result |
|---|---------|-----------------|--------|-------------------|
| Frequency range   | 13.1(a) | 13.1(a)(i)      | X      | Compliant         |
| Rate of Change of Frequency (ROCOF) Withstand capability, df/dt | 13.1(b) | 13.1(b)         | х      | Compliant         |
| Remote cessation of active power                                | 13.6    | 13.6            | х      | Compliant         |
| Limited Frequency Sensitive Mode – Over frequency (LFSM-O)      | 13.2    | 13.2(a).(b).(f) | х      | Compliant         |



This is an Appendix to Certificate of Conformity Number: CN-PV-230299

| Model                      | ASN-5TL                            | ASN-6TL   | ASN-8TL | ASN-10TL |  |  |
|----------------------------|------------------------------------|-----------|---------|----------|--|--|
| PV Input                   |                                    |           |         |          |  |  |
| Max. input voltage         |                                    | 1100V     |         |          |  |  |
| MPPT voltage range         |                                    | 200-1000V |         |          |  |  |
| Max. input current         | 16A/16A                            |           |         |          |  |  |
| Max. short circuit current | 20A/20A                            |           |         |          |  |  |
| Output AC                  |                                    |           |         |          |  |  |
| Rated output power         | 5kW                                | 6kW       | 8kW     | 10kW     |  |  |
| Max. apparent output power | 5.5kVA                             | 6.6kVA    | 8.8kVA  | 11kVA    |  |  |
| Rated grid voltage         | 220V/380V, 230V/400V, 3/N/PE       |           |         |          |  |  |
| Rated grid frequency       | 50Hz                               |           |         |          |  |  |
| Max. output current        | 8.4A                               | 10.0A     | 13.3A   | 16.7A    |  |  |
| Power factor               | 1 default (0.8 leading0.8 lagging) |           |         |          |  |  |
| Ambient temperature range  | -30+60°C                           |           |         |          |  |  |
| Degree of protection       | IP66                               |           |         |          |  |  |
| Software Version           | DSP: D2301; ARM: A2301             |           |         |          |  |  |



This is an Appendix to Certificate of Conformity Number: CN-PV-230299

| Model                      | ASN-12TL                           | ASN-15TL            | ASN-17TL |  |
|----------------------------|------------------------------------|---------------------|----------|--|
| PV Input                   | 1                                  |                     |          |  |
| Max. input voltage         | 1100V                              |                     |          |  |
| MPPT voltage range         | 200-1000V                          |                     |          |  |
| Max. input current         | 16A/16A 32A/16A 32A                |                     | 32A/32A  |  |
| Max. short circuit current | 20A/20A                            | 40A/20A             | 40A/40A  |  |
| Output AC                  |                                    |                     |          |  |
| Rated output power         | 12kW                               | 15kW                | 17kW     |  |
| Max. apparent output power | 13.2kVA                            | 16.5kVA             | 18.7kVA  |  |
| Rated grid voltage         | 220V/                              | 380V, 230V/400V, 3/ | N/PE     |  |
| Rated grid frequency       | 50Hz                               |                     |          |  |
| Max. output current        | 20.1A                              | 25.1A               | 28.3A    |  |
| Power factor               | 1 default (0.8 leading0.8 lagging) |                     |          |  |
| Ambient temperature range  | -30+60°C                           |                     |          |  |
| Degree of protection       | IP66                               |                     |          |  |
| Software Version           | DSP: D2301; ARM: A2301             |                     |          |  |



This is an Appendix to Certificate of Conformity Number: CN-PV-230299

| Model                      | ASN-20TL                           | ASN-23TL | ASN-25TL |  |
|----------------------------|------------------------------------|----------|----------|--|
| PV Input                   |                                    |          |          |  |
| Max. input voltage         | 1100V                              |          |          |  |
| MPPT voltage range         | 200-1000V                          |          |          |  |
| Max. input current         | 32A/32A                            |          |          |  |
| Max. short circuit current | 40A/40A                            |          |          |  |
| Output AC                  |                                    |          |          |  |
| Rated output power         | 20kW                               | 23kW     | 25kW     |  |
| Max. apparent output power | 22kVA                              | 25.3kVA  | 27.5kVA  |  |
| Rated grid voltage         | 220V/380V, 230V/400V, 3/N/PE       |          |          |  |
| Rated grid frequency       | 50Hz                               |          |          |  |
| Max. output current        | 33.3A                              | 38.3A    | 39.8A    |  |
| Power factor               | 1 default (0.8 leading0.8 lagging) |          |          |  |
| Ambient temperature range  | -30+60℃                            |          |          |  |
| Degree of protection       | IP66                               |          |          |  |
| Software Version           | DSP: D2301; ARM: A2301             |          |          |  |